

Aluminum Electrolytic Capacitor Specification				
Series	KR2	25 V 22 μ F	Part No.	KR2-025V220MC070-T/A5.0
Customer No.	/		Case size	Φ D 5 X L 7
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 85 °C	
	Capacitance tolerance		\pm 20% (20°C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.14 (20°C , 120Hz)	
	Leakage current (MAX)		(Less than) 5.5 μ A (20°C 25 V 2 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		50mArms (120Hz , 85°C)	
	Load life		1000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with a sleeve and two leads. Dimensions include a height of 5+0.5 MAX, a length of 7 + 1.0max, a lead length of 15min, and a lead diameter of 4min. The sleeve diameter is Φ0.45\pm0.05. Labels include 'Sleeve', 'Copper clad steel wire(tinned)', 'Markings', and 'Flat Rubber'. A top view shows a circular capacitor with a lead space of 2.0\pm0.5. A note specifies: 【Remarks:Taping space: 2.5 (+0.8-0.2)】. The unit is mm.</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG