

# Encapsulated Transformers



Type **EI 30/12,5** Output Power **1,5 VA**

El-Kom Code	Secondary [V]	Current [A]	No-Load [Output]	Pin Pr/Sec
RN130321	6	0,250	9,30	1-5/7-9
RN130322	7,5	0,200	11,63	1-5/7-9
RN130323	9	0,167	13,95	1-5/7-9
RN130324	12	0,125	18,60	1-5/7-9
RN130325	15	0,100	23,25	1-5/7-9
RN130326	18	0,083	27,90	1-5/7-9
RN130327	24	0,063	37,20	1-5/7-9
RN130328	30	0,050	46,50	1-5/7-9
RN130341	2 x 6	2 x 0,125	2 x 9,30	1-5/6-7,9-10
RN130342	2 x 7,5	2 x 0,100	2 x 11,63	1-5/6-7,9-10
RN130343	2 x 9	2 x 0,083	2 x 13,95	1-5/6-7,9-10
RN130344	2 x 12	2 x 0,063	2 x 18,60	1-5/6-7,9-10
RN130345	2 x 15	2 x 0,050	2 x 23,25	1-5/6-7,9-10
RN130346	2 x 18	2 x 0,042	2 x 27,90	1-5/6-7,9-10
RN130347	2 x 24	2 x 0,031	2 x 37,20	1-5/6-7,9-10

## Specifications

Potted under vacuum | Split-Bobbin Winding  
**Design** : acc. to VDE 0570, EN 61558  
**Safety Class** : II  
**Protection Index** : IP 00  
**Ambient Temp.** : ta=60°C  
**Test Voltage** : 4000V/50Hz  
 (between input & output)  
**Short Circuit Strength:** Sort-Circuit-Proof  
**Primary** : 230 V

## Dimensions (mm)

Pin: Ø 0,8

