




PSF-08A-E



PSF-08A-E







**Specification**

Rated load	Current / Voltage	A/VAC	10/300
Dielectric strength	Coil/Contact	V/S	4000
	Between contacts	V/S	2500
External connection wire	AWG/mm <sup>2</sup>		20-14/0.5-2.5
Screw torque	Nm		0.8
Terminal protection degree			IP20

**Matched relay**

Socket model	Relay model	Metal Clip	Module	DIN clip
PSF-08A-E	JQX-14FC/14FF 1Z	K-25C		35
	JQX-14FL 1Z 10A	K-20L		
	JQX-115F 1Z 10A	K-15F		

**Outline dimension, Wiring diagram**



PSF-14A-E



PSF-14A-E



**Specification**

Rated load	Current / Voltage	A/VAC	10/300
Dielectric strength	Coil/Contact	V/S	4000
	Between contacts	V/S	2500
External connection wire	AWG/mm <sup>2</sup>		20-14/0.5-2.5
Screw torque	Nm		0.8
Terminal protection degree			IP20

**Matched relay**

Socket model	Relay model	Metal Clip	Module	DIN clip
PSF-14A-E	JQX-14FC/14FF 2Z	K-25C		35
	JQX-14FL 2Z	K-20L		
	JQX-14FL 1Z 16A			
	JQX-115F 2Z	K-15F		
	JQX-115F 1Z 16A			

**Outline dimension, Wiring diagram**

